



ALL-OUT® System

NEXT GENERATION OF HOPPER BINS



Leadership Through Innovation®
for a New Feed Storage Standard

Exclusive features for ALL-OUT® bin performance

Brock reinvented the feed bin with the introduction of its next generation of hopper bins. Brock's Next Generation Feed Bin raises a new industry standard for excellence and value. Added together, the innovative features of the Next Generation Feed Bin comprise Brock's ALL-OUT® system to provide solutions for better productivity in your operation.

Product Features

- **SPRING-LOCK® Lid** provides a positive, spring-aided closing action, yet is easy to open with one hand.
- **40° Roof** matches the natural incline angle of repose for stored feed to maximize usable feed storage capacity.
- **HYDROSHIELD® Weather Guard** directs moisture to drip off the bin's sidewall and keeps it off the bin's hopper and boot.
- **ACCESS PLUS® Hopper Access Door** permits easy clean out of the bin from the ground. The Door retrofits into previous BROCK® Feed Bin models too.
- **Digital WEIGH-MATIC® Scale System** uses temperature-compensated load cells to give highly accurate weights for feed stored in individual feed bins.
- **Automatic boot slide actuator system** automatically closes boot slide shut off on empty bin while opening second bin in tandem systems. Manual actuator is also available.



Optional Ladder Security Door

Product Advantages

- **SPRING-LOCK® Lid** resists wind and keeps out snow and rain. When open, the lid slides down and out of the way of feed truck's auger.
- **SPRING-LOCK® Lid and ACCESS PLUS® Door** aid in biosecurity by allowing remote bin opener location and by easing cleaning chores.
- **HYDROSHIELD® Guard** results in less water on bin hopper and boot.
- **Automatic boot slide actuator** on a tandem feed bin system helps keep birds or animals from missing a feeding.

Warranty and Service

For the dealer nearest you, call the Brock Customer Service Department at 574-658-4191 or go to the dealer finder on www.brockgrain.com.



SPRING-LOCK®
Feed Bin Lid & Opener (patented)



HYDROSHIELD®
Weather Guard



Sturdy Ladder System includes a
convenient handrail (patented)



Optional ACCESS PLUS®
Hopper Access Door (patented)



Red Translucent Boot Transition offers
highest durability and even flow

HOPPER BINS—40° Roof & HYDROSHIELD®

MODEL NUMBER	CAPACITY 40 LB./CUBIC FT. TONS	CUBIC FEET	HEIGHT TO FILL FEET-INCHES
6' diameter bins w/60° hopper			
45-00601	3.1	156.9	11' 6"
45-00602	4.6	231.9	14' 2"
45-00603	6.1	306.9	16' 10"
45-00604	7.6	381.9	19' 6"
7' diameter bins w/67° hopper			
45-00721	4.9	245.6	14' 9"
45-00722	6.9	347.0	17' 5"
45-00723	9.0	448.4	20' 1"
45-00724	11.0	549.8	22' 9"
45-00725	13.0	651.2	25' 5"
45-00726	15.1	752.6	28' 1"
9' diameter bins w/60° hopper			
45-00901	8.6	427.6	15' 7"
45-00902	12.0	597.6	18' 3"
45-00903	15.4	767.6	20' 11"
45-00904	18.8	937.6	23' 7"
45-00905	22.2	1107.6	26' 3"



Optional Digital WEIGH-MATIC®
Load Cells



Optional Automatic Boot Slide
Actuator System

MODEL NUMBER	CAPACITY 40 LB./CUBIC FT. TONS	CUBIC FEET	HEIGHT TO FILL FEET-INCHES
9' diameter bins w/60° hopper (continued)			
45-00906	25.6	1277.6	28' 11"
45-00907	28.9	1442.6	31' 7"
12' diameter bins w/60° hopper			
45-01201	17.8	887.5	19' 5"
45-01202	23.7	1186.0	22' 1"
45-01203	29.7	1484.4	24' 9"
45-01204	35.7	1782.9	27' 5"
45-01205	41.6	2081.3	30' 1"
45-01206	47.6	2379.9	32' 9"
45-01207	53.6	2678.3	35' 5"
15' diameter bins w/60° hopper			
45-01502	41.5	2076.0	25' 10"
45-01503	50.9	2542.5	28' 6"
45-01504	60.2	3008.6	31' 2"
45-01505	69.5	3474.9	33' 10"
45-01506	78.8	3941.2	36' 6"
45-01507	88.2	4407.5	39' 2"
45-01508	97.5	4873.8	41' 10"



Brock Grain Systems

Chore-Time Brock International

Divisions of CTB, Inc., Milford, IN • Kansas City, MO • Frankfort, IN
 Phone: 574.658.4191 or +1.574.658.9323 (International)
 Internet: www.BrockGrain.com or www.ctbworld.com
 E-mail: Brock@BrockGrain.com